



**Digital Weighing Indicator / Controller with 3 relay O/ps, 3 Digital Inputs, Analog 0-10 V or 4-20 mA Output, RS 232 or RS 422 Serial Interface.**

**Standard Features: MAX / MIN Alarm Outputs, PEAK VALUE sensing, REAL TIME CLOCK.**

**Special Function Modes selectable through Software Configuration.**

**Mode 1: One Component Coarse-Fine-Discharge Controller.**

**Mode 2: Two Component Feed 1-Feed 2-Discharge Controller. [With Dribble Function on Feed O/ps]**

**Mode 3: Loss in Weight Feed Controller: Feed 1-Feed 2-Discharge**

**Mode 4: CHECK WEIGHER Controller.**

### **XK3190-C8 Salient Features**

- High speed A/D conversion technology [80 samples/second].
- Ideal for electronic batching systems, electronic fix-value scale and electronic check weigher.
- Max. and Min. limit alarms
- Peak value monitoring.
- 3 external inputs – for START / STOP / FEED / DISCHARGE.
- 3 Relay outputs
- High precision A/D conversion with readability 1/30000
- 5 points nonlinearity correction.[Multi-point Calibration].
- Zero tracking, range for zero (automatic and manual) is free to be set
- 90-230 volts AC operation
- Panel Mount : 144 mm Width, 96 mm Height, 90 mm Depth